

[Get a Quote](#)

Overview

Cisco Catalyst 3750X-48P Switch Layer 3 - 48 x 10/100/1000 Ethernet PoE+ Ports - IP Base - Managed - Stackable

Quick Specification

Product Code	WS-C3750X-48P-S
Product Type	Managed, Stackable 48 ports L3 Switch
Form Factor	Fixed, Rack Mountable 1U, Stackable/Clustering
Switch Port density - Uplinks	48 x 10/100/1000 Ethernet Ports
Power Over Ethernet (PoE)	Yes
Max Number of Stacks	9
DRAM Memory	256 MB
Flash Memory	128 MB Flash
Width	44.5 cm
Depth	46 cm
Height	4.5 cm
Weight	7.5 kg

Product Details:

The Front Panel:



The Back Panel:



Get more information:

Do you have any question about the WS-C3750X-48P-S?

Contact us now via e-mail: info@hi-network.com

Specific Data Sheet:

Manufacturer:	Cisco
Product Name	WS-C3750X-48P-S
Product Type	Managed, Stackable 48 ports L3 Switch
Form Factor	Fixed, Rack Mountable 1U, Stackable/Clustering
Switch Port density - Uplinks	48 x 10/100/1000 Ethernet Ports
Power Over Ethernet (PoE)	Yes
Max Number of Stacks	9
Routing Protocol	RIP-1, RIP-2, HSRP, static IP routing, RIPng
Remote Management Protocol	SNMP 1, SNMP 2, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, TFTP, SSH, CLI
Authentication Method	Kerberos, Secure Shell (SSH), RADIUS, TACACS+
Features	Hot swap module replacement, Layer 3 switching, Layer 2 switching, dynamic IP address assignment , DHCP support, power over Ethernet (PoE), auto-negotiation, ARP support, trunking, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, Syslog support, traffic shaping, Broadcast Storm Control, High Availability, Multicast Storm Control, Unicast Storm Control, Rapid Spanning Tree Protocol (RSTP) support, DHCP snooping, Dynamic Trunking Protocol (DTP) support, Port Aggregation Protocol (PAgP) support, Access Control List (ACL) support, Quality of Service (QoS), Jumbo Frames support, MLD snooping, Dynamic ARP Inspection (DAI), PoE+, Per-VLAN Spanning Tree Plus (PVST+), EIGRP Stub Routing
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ae, IEEE 802.3at
DRAM Memory	256 MB

WS-C3750X-48P-S Datasheet



HI-NETWORK.com
Your Global Original Network Supplier

Flash Memory	128 MB Flash
LED Status Lights Indicators	Port status, link activity, port transmission speed, port duplex mode, power, system
Connectivity / Expansion Slots	
Interfaces	48 x 10Base-T/100Base-TX/1000Base-T - RJ-45 - PoE USB : 1 x 4 PIN USB Type A 1 x console - mini-USB Type B - management 1 x RS-232 - RJ-45 - management 1 x 10Base-T/100Base-TX - RJ-45 - management Network stack device : 2 x
Expansion Slot(s)	1 (total) / 1 (free) x Expansion Slot
Power Supply Specifications	
Power Device	Power supply - redundant - plug-in module
Installed Qty	1 (installed) / 2 (max)
Power Redundancy	Optional
Power Redundancy Scheme	1+1 (with optional power supply)
Voltage Required	AC 120/230 V (50/60 Hz)
Features	Redundant Power System (RPS) connector
Dimensions / Weight / Miscellaneous	
Width	44.5 cm
Depth	46 cm
Height	4.5 cm
Weight	7.5 kg
Rack Mounting Kit	Optional
MTBF	139,913 hour(s)
Compliant Standards	CE, TUV GS, CISPR 22 Class A, GOST, cUL, NOM, VCCI Class A ITE, EN55022 Class A, CB, AS/NZS 60950-1, AS/NZ 3548 Class A, CCC, RoHS, UL 60950-1, IEC 60950-1, EN 60950-1, KCC, FCC Part 15 A, CSA C22.2 No. 60950-1
System Software	
Software Included	Cisco IOS IP Base
Manufacturer Warranty	
Service & Support	Limited lifetime warranty
Service & Support Details	Limited warranty - lifetime Limited warranty - power supply and fans - 5 years New releases update



Want to Buy

Get a Quote



[Learn More](#) about Hi-Network



[Search](#) our Resource Library



[Follow](#) us on LinkedIn



Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/people/echo.hinetwork)

WhatsApp Business: +8618057156223