



Overview

CloudEngine 5800 series switches deliver high gigabit access, enabling enterprises and carriers to build cloud-oriented data center networks. Featuring 40 GE uplink ports and flexible airflow capabilities, the switches are capable of forming a 9-member stack system and are well-suited for either the aggregation or the access layer. Coupled with CloudEngine 16800 or 12800 series switches, CloudEngine 5800 enables enterprises to build networks that are scalable, simplified, open — and secure.

Quick Specification

Table 1 shows the quick specification of CE5855-24T4S2Q-EI.

Model	CE5855-24T4S2Q-EI
Part Number	02350GTX
Software Version	V100R005C10 and later
Fixed GE interfaces	24*10/100/1000BASE-T
Fixed 10GE interfaces	4*10GE SFP+
Fixed 40GE interfaces	2*40GE QSFP+ A 40GE interface can be split into four 10GE interfaces.
Fixed 100GE interfaces	None
Base-T Ports	24
SFP+ Ports	4
QSFP+ Ports	2
Switching Capacity	288 Gbit/s
Forwarding Rate	215 Mpps
Power module type	Pluggable AC or DC power module, 1+1 backup supported
Rated voltage range	100 V AC to 240 V AC, 50/60 Hz -48 V DC to -60 V DC
Maximum power consumption	75W
Airflow	Front-to-back or back-to-front, depending on the fan modules and power modules used in the chassis
Dimensions (W x D x H)	442 mm x 420 mm x 43.6 mm
Weight (fully loaded)	8.1 kg (17.8 lb)



Figure 1 shows the appearance of CE5855-24T4S2Q-EI.



Product Details

Figure 2 shows the CE5855-24T4S2Q-EI front view (port side).



Note:

(1)	Twenty-four 10/100/1000BASE-T Ethernet electrical ports
(2)	Four 10GE SFP+ Ethernet optical ports
(3)	Two 40GE QSFP+ Ethernet optical ports

Figure 3 shows the CE5855-24T4S2Q-EI rear view (power supply side).



Note:

(1)	Power supply slot 1	(5)	Fan slot 2
(2)	Fan slot 1	(6)	Power supply slot 2
(3)	Console port	(7)	USB port



(4)	Barcode label	(8)	ETH management port (RJ45)
-----	---------------	-----	----------------------------

The Modules

Table 2 shows the recommended elements for the CE5855-24T4S2Q-EI.

Model	Description
GE-SFP Optical Transceiver	
eSFP-GE-SX-MM850	Optical Transceiver, eSFP, GE, Multi-mode Module (850nm, 0.55km, LC)
SFP-GE-LX-SM1310	Optical Transceiver, eSFP, GE, Single-mode Module (1310nm, 10km, LC)
S-SFP-GE-LH40-SM1310	Optical Transceiver, eSFP, GE, Single-mode Module (1310nm, 40km, LC)
S-SFP-GE-LH40-SM1550	Optical Transceiver, eSFP, GE, Single-mode Module (1550nm, 40km, LC)
10G-SFP+ Optical Transceiver	
SFP-10G-USR	10GBase-USR Optical Transceiver, SFP+, 10G, Multi-mode Module (850nm, 0.1km, LC)
OMXD30000	Optical Transceiver, SFP+, 10G, Multi-mode Module (850nm, 0.3km, LC)
GE Copper Transceiver	
SFP-1000BaseT	Electrical Transceiver, SFP, GE, Electrical Interface Module (100m, RJ45)

Compare to Similar Items

Table 3 shows the comparison of CE5855-24T4S2Q-EI and CE5855-48T4S2Q-EI.

Model	CE5855-24T4S2Q-EI	CE5855-48T4S2Q-EI
Software Version	V100R005C10 and later	V100R005C10 and later
Fixed GE interfaces	24*10/100/1000BASE-T	48*10/100/1000BASE-T
Fixed 10GE interfaces	4*10GE SFP+	4*10GE SFP+
Fixed 40GE interfaces	2*40GE QSFP+ A 40GE interface can be split into four 10GE interfaces.	2*40GE QSFP+ A 40GE interface can be split into four 10GE interfaces.
Fixed 100GE interfaces	None	None
Base-T Ports	24	48
SFP+ Ports	4	4
QSFP+ Ports	2	2
Switching Capacity	288 Gbit/s	336 Gbit/s
Forwarding Rate	215 Mpps	252 Mpps
Maximum power consumption	75W	103W





Get more information

Do you have any question about the CE5855-24T4S2Q-EI (02350GTX)?

Contact us now via info@hi-network.com.

Specification

CE5855-24T4S2Q-EI Specification	
Base-T Ports	24
SFP+ Ports	4
QSFP+ Ports	2
Switching Capacity	288 Gbit/s
Forwarding Rates	215 Mpps
Airflow Design	Front-to-back or back-to-front
Device Virtualization	iStack Super Virtual Fabric (SVF)
Network Virtualization	M-LAG TRILL (CE5855 & CE5850)
VM Awareness	Agile Controller
SDN	Open Programmability System (OPS)
Traffic Analysis	NetStream sFlow
VLAN	Adding access, trunk, and hybrid interfaces to VLANs Default VLAN QinQ MUX VLAN GVRP
ACL	ingress: 4.5k egress: 1k
MAC Address Table	maximum: 64k Dynamic learning and aging of MAC addresses Static, dynamic, and black hole MAC address entries Packet filtering based on source MAC addresses MAC address limiting based on ports and VLANs
ARP (maximum)	54k
IPv4 FIB (maximum)	32k
IP Routing	IPv4 routing protocols, such as RIP, OSPF, BGP, and IS-IS IPv6 routing protocols, such as RIPng, OSPFv3, IS-ISv6, and BGP4+ (not supported by CE5855)
IPv6 FIB (maximum)	-





IPv6	<p>IPv6 Neighbor Discovery (ND) (not supported by CE5855)</p> <p>Path MTU Discovery (PMTU) (not supported by CE5855)</p> <p>TCP6, ping IPv6, tracer IPv6, socket IPv6, UDP6, and Raw IP6</p>
Multicast FIB (maximum)	2k
Multicast	<p>IGMP, PIM-SM, PIM-DM, MSDP, and MBGP</p> <p>IGMP snooping</p> <p>IGMP proxy</p> <p>Fast leave of multicast member interfaces</p> <p>Multicast traffic suppression</p> <p>Multicast VLAN</p>
Reliability	<p>LACP</p> <p>STP, RSTP, VBST, MSTP</p> <p>BPDU protection, root protection, and loop protection</p> <p>Smart Link and multi-instance</p> <p>DLDP</p> <p>ERPS (G.8032)</p> <p>VRRP, VRRP load balancing, and BFD for VRRP</p> <p>BFD for BGP/IS-IS/OSPF/Static route</p>
QoS	<p>Traffic classification based on Layer 2 headers, Layer 3 protocols, Layer 4 protocols, and 802.1p priority</p> <p>Actions of ACL, CAR, re-marking, and scheduling</p> <p>Queue scheduling algorithms, including PQ, WRR, DRR, PQ + WRR, and PQ + DRR</p> <p>Congestion avoidance mechanisms, including WRED and tail drop</p> <p>Traffic shaping</p>
Configuration and Maintenance	<p>Console, Telnet, and SSH terminals</p> <p>Network management protocols, such as SNMPv1/v2c/v3</p> <p>File upload and download through FTP and TFTP</p> <p>BootROM upgrade and remote upgrade</p> <p>802.3az Energy Efficient Ethernet (EEE)</p> <p>Hot patches</p> <p>User operation logs</p> <p>Zero-Touch Provisioning (ZTP)</p>
Security and Management	<p>802.1x authentication</p> <p>Command line authority control based on user levels, preventing unauthorized users from using commands</p> <p>DoS, ARP, and ICMP attack defenses</p> <p>Port isolation, port security, and sticky MAC</p> <p>Binding of the IP address, MAC address, interface number, and VLAN ID</p> <p>Authentication methods, including AAA, RADIUS, and HWTACACS</p> <p>Remote Network Monitoring (RMON)</p>
Dimensions (W x D x H)	442 mm x 420 mm x 43.6 mm
Weight (fully loaded)	8.1 kg (17.8 lb)
Environmental Parameters	<p>Operating temperature: 0°C to 40°C (32°F to 104°F) (0m to 1,800m)</p> <p>Storage temperature: -40°C to 70°C (-40°F to 158°F)</p> <p>Relative humidity: 5% to 95%, non-condensing</p>





Operating Voltage	AC: 90V to 264V DC: -38.4V to -72V
Maximum Power Consumption	75W

Want to Buy

[Get a Quote](#)[Learn More](#) about Hi-Network[Search](#) our Resource Library[Follow](#) us on LinkedInContact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: [echo.hinetwork](https://www.skype.com/addtocontactlist/echo.hinetwork)

WhatsApp Business: +8618057156223

